NSN 5930-01-118-6799

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-118-6799

Inside Diameter:
0.500 inches single connection
Overall Length:
3.500 inches
Overall Height:
6.500 inches
Overall Width:
2.850 inches
Unthreaded Mounting Hole Diameter:
0.265 inches
Longest Horizontal Distance Between Mounting Centers:
2.720 inches
Longest Vertical Distance Between Mounting Centers:
2.720 inches
Pressure Switch Type:
Gage
Operating Tempurature Rating:
Between -30.0 degrees fahrenheit and 160.0 degrees fahrenheit
Mounting Method:
Unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Proof Pressure:
5000.00 pounds per square inch gage
Thread Size:
0.500 inches single pressure connection
Mounting Facility Pattern:
Two position diagonal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
500.0 milliamperes resistive load fourth voltage and 40.0 milliamperes inductive load fourth voltage
Contact Adjustability:
Actuation point adjustable and deactuation point adjustable
Contact Adjustment Range:

Contact Adjustment Type:

+15.00/+150.00 actuation point pounds per square inch gage and +9.00/+144.00 deactuation point pounds per square inch gage

Internal actuation point hex nut with scale

NSN 5930-01-118-6799

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts: 600.0 ac at sea level third voltage Pressure Connector Type: Plain, threaded internal single connection Media For Which Designed: Gas or liquid Style Designator: Rectangular Thread Series Designator: Npt single pressure connection Shelf Life: N/a Unit Of Measure: ---

Demilitarization:

No Fiig: A048b0