NSN 5930-01-118-6804

Sensitive Switch - Page 1 of 2

Bushing/hole mounted

Overall Length: 1.880 inches Overall Height:



View Online at https://aerobasegroup.com/nsn/5930-01-118-6804

Body Style:

2.100 inches **Overall Width:** 0.610 inches **Bushing Length:** 0.800 inches **Body Width:** 0.610 inches **Body Height:** 1.050 inches **Case Material: Plastic Actuator Style:** Round **Actuator Diameter:** 0.326 inches **Actuator Height:** 0.250 inches **Actuator Free Position Height:** 1.050 inches **Maximum Voltage Rating In Volts:** 250.0 ac **End Application:** Trk frklt 90031 **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing and unthreaded hole Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.469 inches **Nonpile-up Contact Arrangement:** 2 two circuit, double break/double make, one position momentary single switch unit **Switch Release Force:** 4.0 ounces **Switch Actuating Force:** 17.0 ounces

NSN 5930-01-118-6804

Sensitive Switch - Page 2 of 2



Δ	ctu	ato	- М	ΛV/	am.	۵ni	ŀ
н	CLU	alu	IVI	OVE	2111		L.

0.060 pretravel inches and 0.187 overtravel inches and 0.028 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

8 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0