

View Online at <https://aerobasegroup.com/nsn/5930-01-118-6804>

Body Style:

Bushing/hole mounted

Overall Length:

1.880 inches

Overall Height:

2.100 inches

Overall Width:

0.610 inches

Bushing Length:

0.800 inches

Body Width:

0.610 inches

Body Height:

1.050 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.326 inches

Actuator Height:

0.250 inches

Actuator Free Position Height:

1.050 inches

Maximum Voltage Rating In Volts:

250.0 ac

End Application:

Trk frklt 90031

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing and unthreaded hole

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

17.0 ounces

Actuator Movement:

0.060 pretravel inches and 0.187 overtravel inches and 0.028 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

8 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0