# NSN 5930-01-118-7882

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-118-7882

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
2.751 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.688 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.090 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
White single actuator
Actuator Inscription:
Kwr 37 3 single actuator
Maximum Voltage Rating In Volts:
28.0 dc
End Application:
An/bsc-1
Mounting Surface To Terminal End Distance:
2.620 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:

Rfi shielding

## NSN 5930-01-118-7882

Push Switch - Page 2 of 2



### **Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

#### **Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

**Precious Material And Location:** 

Contacts gold

### **Terminal Type And Quantity:**

5 tab, solder lug and 6 turret

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0