NSN 5930-01-118-7883

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-118-7883

| Body Style: |
|---|
| Bushing mounted |
| Overall Length: |
| 2.150 inches |
| Overall Height: |
| 0.605 inches |
| Overall Width: |
| 0.605 inches |
| |
| Body Diameter: |
| 0.560 inches |
| Bushing Length: |
| Between 0.315 inches and 0.345 inches |
| Actuator Height: |
| Between 0.785 inches and 0.815 inches |
| Actuator Color: |
| White single actuator |
| Illuminated Actuator Color: |
| Green single actuator |
| Actuator Inscription: |
| Bypass single actuator |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| End Application: |
| An/slq-17 (v) |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Features Provided: |
| Actuator seal and rfi shielding |
| Thread Size: |
| 0.438 inches |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| $7.000 \ amperes \ resistive \ dc \ and \ 4.000 \ amperes \ inductive \ dc \ and \ 12.500 \ amperes \ lamp \ dc \ and \ 4.000 \ amperes \ motor \ dc$ |
| Thread Series Designator: |
| Unf |
| Terminal Type And Quantity: |
| 2 tab, solder lug and 3 turret |
| Shelf Life: |

N/a

NSN 5930-01-118-7883

Push Switch - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A053a0