NSN 5930-01-118-8406

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-118-8406

| Body Style: |
|---|
| Panel mount |
| Hazardous Locations/environmental Protection: |
| Moisture proof and shock proof |
| Overall Length: |
| 0.755 inches |
| Overall Height: |
| 3.060 inches |
| Overall Width: |
| 0.755 inches |
| Body Length: |
| 0.755 inches |
| Body Width: |
| 0.755 inches |
| Body Height: |
| 2.250 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| 0.755 inches |
| Actuator Style: |
| Rectangular |
| Actuator Width: |
| 0.755 inches |
| Actuator Color: |
| Amber single actuator and green single actuator |
| Illuminated Actuator Color: |
| Amber single actuator and green single actuator |
| Actuator Inscription: |
| Load/loaded single actuator |
| Illuminated Actuator Color Sequence: |
| Upper half of actuator amber lower half of actuator green |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |

Nonpile-up Contact Arrangement:

Actuator seal

4 pole, double throw, one position momentary single switch unit

NSN 5930-01-118-8406

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac and 1.500 amperes lamp ac

| 3.000 amperes resistive de and 2.500 amperes inductive de and 1.500 amperes famp de ai |
|--|
| inductive ac and 1.500 amperes lamp ac |
| Special Features: |
| Horizontal split lens |
| Precious Material And Location: |
| Contact surfaces gold and contacts silver |
| Unable To Decode: |
| Unable to decode and unable to decode |
| Terminal Type And Quantity: |
| 19 pin |
| Shelf Life: |
| N/a |

Demilitarization:

Unit Of Measure:

No

Fiig:

A053a0