NSN 5930-01-118-9204

Pressure Switch - Page 1 of 2

square inch

Contact Voltage Rating In Volts: 250.0 ac at sea level second voltage



View Online at https://aerobasegroup.com/nsn/5930-01-118-9204

Inread Class:
3b single pressure connection
Inside Diameter:
0.438 inches single connection
Thread Length:
12.70 millimeters single pressure connection
Hazardous Locations/environmental Protection:
General purpose-nema type 1
Overall Length:
82.6 millimeters
Body Diameter:
57.4 major centimeters
Body Length:
55.1 millimeters
Overall Diameter:
84.8 millimeters
End Application:
Mk75mod0 gun 44114
Pressure Switch Type:
Gage
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
24 single threaded bushing
Contact Action Stimulus:
Increase
Thread Size:
0.625 inches single threaded bushing
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
5.0 amperes resistive load third voltage and 2.5 amperes inductive load third voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
90.00 actuation point pounds per square inch and 60.00 deactuation point pounds per square inch and 30.00 differential point pounds per

NSN 5930-01-118-9204

Pressure Switch - Page 2 of 2



Pressure Connector Type:
Plain, threaded internal single connection
Media For Which Designed:
Gas
Style Designator:
Cylindrical
Thread Series Designator:
Unf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

Fiig: A048b0