

View Online at <https://aerobasegroup.com/nsn/5930-01-118-9206>

Thread Class:

3a single pressure connection

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

3.500 inches

Overall Diameter:

1.120 inches

End Application:

Envir system 76301

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 300.0 degrees fahrenheit

Mounting Method:

Outlet connection

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

185.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Sensing Element Burst Pressure:

250.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

1.3 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

26.00 actuation point pounds per square inch gage and 23.00 deactuation point pounds per square inch gage and 3.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Swivel, plain, threaded external single connection

Media For Which Designed:

Gas

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0