# NSN 5930-01-118-9219

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-118-9219

# **Body Style:**

Panel mount

# Hazardous Locations/environmental Protection:

Moisture proof

# **Overall Length:**

3.060 inches

#### **Overall Height:**

0.740 inches

#### **Overall Width:**

0.740 inches

#### **Body Length:**

0.740 inches

# **Body Width:**

0.740 inches

#### Case Material:

Metal

# Actuator Length:

0.740 inches

# Actuator Style:

Rectangular

## Actuator Width:

0.740 inches

#### Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

# **End Application:**

An/slq-17 (v) 05869

#### Inclosure Type:

Fully enclosed

## **Mounting Method:**

Panel

## **Features Provided:**

Rfi shielding

#### **Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

#### Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac

# Special Features:

Full display lens

# **Terminal Type And Quantity:**

11 tab, solder lug

#### Shelf Life:

N/a

# NSN 5930-01-118-9219

Push Switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

