

View Online at <https://aerobasegroup.com/nsn/5930-01-119-2098>

Overall Length:

3.500 inches

Overall Height:

5.930 inches

Overall Width:

3.060 inches

Body Height:

3.500 inches

Unthreaded Mounting Hole Diameter:

0.270 inches

Longest Horizontal Distance Between Mounting Centers:

2.720 inches

Longest Vertical Distance Between Mounting Centers:

2.720 inches

End Application:

Detroit diesel engine model 12v-71 for portable bubbler machinery onboard 140 ft wtgb class coast guard vessels

Pressure Switch Type:

Absolute

Mounting Method:

Unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained

Terminal Type:

Screw

Contact Load Current Rating:

10.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

8.00 actuation point centimeters per second

Contact Voltage Rating In Volts:

125.0 ac at sea level single voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0