NSN 5930-01-119-2845

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-119-2845

Body Style:					
Bushing mount Hazardous Locations/environmental Protection:					
Weatherproof Overall Length:					
Overall Length: 0.612 inches					
Overall Height:					
1.278 inches					
Overall Width:					
0.512 inches					
Bushing Length:					
0.315 inches					
Body Length:					
0.612 inches					
Body Width: 0.512 inches					
Body Height: 0.354 inches					
Case Material:					
Plastic					
Actuator Style:					
Round					
Actuator Height:					
0.413 inches					
Actuator Position-action Relationship:					
Actuator Position-action Relationship: Up position momentary and down position maintained and center position maintained					
Actuator Position-action Relationship: Up position momentary and down position maintained and center position maintained Actuator Color:					
Actuator Position-action Relationship: Up position momentary and down position maintained and center position maintained Actuator Color: Natural single actuator					
Actuator Position-action Relationship: Up position momentary and down position maintained and center position maintained Actuator Color: Natural single actuator Maximum Voltage Rating In Volts:					
Actuator Position-action Relationship: Up position momentary and down position maintained and center position maintained Actuator Color: Natural single actuator Maximum Voltage Rating In Volts: 250.0 ac and 28.0 dc					
Actuator Position-action Relationship: Up position momentary and down position maintained and center position maintained Actuator Color: Natural single actuator Maximum Voltage Rating In Volts: 250.0 ac and 28.0 dc End Application:					
Actuator Position-action Relationship: Up position momentary and down position maintained and center position maintained Actuator Color: Natural single actuator Maximum Voltage Rating In Volts: 250.0 ac and 28.0 dc End Application: 4920-01-048-8051					
Actuator Position-action Relationship: Up position momentary and down position maintained and center position maintained Actuator Color: Natural single actuator Maximum Voltage Rating In Volts: 250.0 ac and 28.0 dc End Application: 4920-01-048-8051 Mounting Surface To Terminal End Distance:					
Actuator Position-action Relationship: Up position momentary and down position maintained and center position maintained Actuator Color: Natural single actuator Maximum Voltage Rating In Volts: 250.0 ac and 28.0 dc End Application: 4920-01-048-8051 Mounting Surface To Terminal End Distance: 0.511 inches					
Actuator Position-action Relationship: Up position momentary and down position maintained and center position maintained Actuator Color: Natural single actuator Maximum Voltage Rating In Volts: 250.0 ac and 28.0 dc End Application: 4920-01-048-8051 Mounting Surface To Terminal End Distance: 0.511 inches Inclosure Type:					
Actuator Position-action Relationship: Up position momentary and down position maintained and center position maintained Actuator Color: Natural single actuator Maximum Voltage Rating In Volts: 250.0 ac and 28.0 dc End Application: 4920-01-048-8051 Mounting Surface To Terminal End Distance: 0.511 inches Inclosure Type: Fully enclosed					
Actuator Position-action Relationship: Up position momentary and down position maintained and center position maintained Actuator Color: Natural single actuator Maximum Voltage Rating In Volts: 250.0 ac and 28.0 dc End Application: 4920-01-048-8051 Mounting Surface To Terminal End Distance: 0.511 inches Inclosure Type: Fully enclosed Thready Qty Per Inch (tpi):					
Actuator Position-action Relationship: Up position momentary and down position maintained and center position maintained Actuator Color: Natural single actuator Maximum Voltage Rating In Volts: 250.0 ac and 28.0 dc End Application: 4920-01-048-8051 Mounting Surface To Terminal End Distance: 0.511 inches Inclosure Type: Fully enclosed Thready Qty Per Inch (tpi): 40					
Actuator Position-action Relationship: Up position momentary and down position maintained and center position maintained Actuator Color: Natural single actuator Maximum Voltage Rating In Volts: 250.0 ac and 28.0 dc End Application: 4920-01-048-8051 Mounting Surface To Terminal End Distance: 0.511 inches Inclosure Type: Fully enclosed Thready Qty Per Inch (tpi):					

Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary, two positions maintained single switch unit

NSN 5930-01-119-2845

Toggle Switch - Page 2 of 2



Contact Load	l Current	Rating	At Maximum	Rated	Voltage:
Juliaul Luai	a Guileii	ivatiliy	AL WIGAIIIIUIII	Nateu	V Oitage.

4.000 amperes resistive dc and 3.000 amperes resistive ac

Precious Material And Location:

Contacts and terminal surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0