

NSN 5930-01-119-3430 Pressure Switch - Page 1 of 2	AeroBase Group
View Online at https://aerobasegroup.com/nsn/5930-01-119-3430	
Overall Length:	
2.125 inches	
Outside Diameter:	
0.250 inches single connection	
Overall Height:	
4.500 inches	
Overall Width:	
3.500 inches	
Unthreaded Mounting Hole Diameter:	

0.170 inches

Longest Horizontal Distance Between Mounting Centers:

3.062 inches

Longest Vertical Distance Between Mounting Centers:

4.062 inches

Pressure Switch Type:

Gage

Operating Tempurature Rating:

Between -32.0 degrees celsius and 71.0 degrees celsius

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

40.00 inches of water

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Turret

Contact Load Current Rating:

5.0 amperes resistive load single voltage and 3.0 amperes inductive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

0.70 actuation point inches of water and 0.25 deactuation point inches of water

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Plain, unthreaded external single connection

Media For Which Designed:

Gas

NSN 5930-01-119-3430

Pressure Switch - Page 2 of 2



•	_		
Style	D)es	sıan	ator:
,		J. 9.	

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0