# NSN 5930-01-119-5131

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-119-5131

## **Thread Class:**

2a single mounting facility

## **Thread Length:**

0.156 inches single mounting facility

## **Overall Length:**

1.456 inches

#### **Overall Height:**

Between 0.985 inches and 1.015 inches

## Shaft Diameter:

0.124 inches single actuator and 0.126 inches single actuator

#### Shaft Length:

0.394 inches single actuator

## Individual Section Quantity:

1

## **End Application:**

Ts-3852 v2g 80058

## Switch Contact Basic Design:

Nonpile-up symmetrical

## Pole Quantity:

1 single section rear

## Throw Quantity:

5 single section rear

## **Mounting Method:**

Threaded bushing single mounting facility

## **Thread Size:**

0.250 inches single mounting facility

## **Contact Voltage Rating In Volts:**

28.0 dc at sea level

## Switch Actuator Indexing Position Quantity:

5 single actuator

## Shaft Type:

Round single actuator

## Terminal Type:

Printed circuit

## **Contact Switching Action:**

Breaks before makes single section rear

## Switch Actuator Positioning Increment:

60.0 degrees single actuator

## **Detent Rotational Torque Range:**

+12.000/+18.000 inch-ounces single actuator

## Switch Actuator Stop Device Type:

Fixed stop single actuator

# NSN 5930-01-119-5131

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

500.0 milliamperes resistive load dc at sea level

#### **Precious Material And Location:**

Contacts and rotor blade surfaces silver

**Precious Material:** 

Silver

## Style Designator:

Circular wafer, bushing mount

#### **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

#### **Demilitarization:**

No

#### Fiig:

A052b0