

View Online at <https://aerobasegroup.com/nsn/5930-01-119-6186>

Thread Class:

2a single mounting facility

Thread Length:

0.430 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

5.360 inches

Overall Height:

1.250 inches

Overall Width:

1.250 inches

First Flat Length:

0.410 inches 1st actuator

Flat Height:

0.210 inches 1st actuator

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

0.930 inches 2nd actuator

Individual Section Quantity:

3

Nonturn Device Type:

Slotted bushing at 2: 30 o'clock

Operating Temperature Range:

-65.0/+70.0 degrees celsius

End Application:

Envir system

Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

Pole Quantity:

1 2nd section rear

Throw Quantity:

3 2nd section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Features Provided:

Cam actuated and pull to turn

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

337.5 degrees from nonturn device all actuators

Cam Actuated Switch Contact Arrangement:

2 pole, double throw, double break/double make, permanent jumper, both positions maintained single switch 3rd section in-line

Switch Actuator Indexing Position Quantity:

3 1st actuator

Shaft Type:

Round, hollowed, flatted 1st actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes 3rd section in-line

Switch Actuator Positioning Increment:

30.0 degrees 1st actuator

Detent Rotational Torque Range:

+12.000/+64.000 inch-ounces single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level and 2.0 amperes inductive load dc at sea level

Special Features:

With solenoid

Style Designator:

Tap, square frame

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A052b0