

View Online at <https://aerobasegroup.com/nsn/5930-01-119-6186>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.430 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

5.360 inches

**Overall Height:**

1.250 inches

**Overall Width:**

1.250 inches

**First Flat Length:**

0.410 inches 1st actuator

**Flat Height:**

0.210 inches 1st actuator

**Shaft Diameter:**

0.250 inches 1st actuator

**Shaft Length:**

0.930 inches 2nd actuator

**Individual Section Quantity:**

3

**Nonturn Device Type:**

Slotted bushing at 2: 30 o'clock

**Operating Temperature Range:**

-65.0/+70.0 degrees celsius

**End Application:**

Envir system

**Switch Contact Basic Design:**

Nonpile-up symmetrical and nonpile-up nonsymmetrical

**Pole Quantity:**

1 2nd section rear

**Throw Quantity:**

3 2nd section rear

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Features Provided:**

Cam actuated and pull to turn

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

337.5 degrees from nonturn device all actuators

**Cam Actuated Switch Contact Arrangement:**

2 pole, double throw, double break/double make, permanent jumper, both positions maintained single switch 3rd section in-line

**Switch Actuator Indexing Position Quantity:**

3 1st actuator

**Shaft Type:**

Round, hollowed, flatted 1st actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes 3rd section in-line

**Switch Actuator Positioning Increment:**

30.0 degrees 1st actuator

**Detent Rotational Torque Range:**

+12.000/+64.000 inch-ounces single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load dc at sea level and 2.0 amperes inductive load dc at sea level

**Special Features:**

With solenoid

**Style Designator:**

Tap, square frame

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A052b0