

View Online at <https://aerobasegroup.com/nsn/5930-01-120-3591>

**Hazardous Locations/environmental Protection:**

Moisture resistant and vibration resistant

**Overall Length:**

4.220 inches

**Outside Diameter:**

0.250 inches single connection

**Body Diameter:**

1.560 inches

**Overall Diameter:**

1.870 inches

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between -45.6 degrees celsius and 71.0 degrees celsius

**Mounting Method:**

Inlet connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

1000.00 pounds per square inch gage

**Thread Size:**

0.250 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

5.0 amperes resistive load single voltage and 3.0 amperes inductive load single voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

29.50 actuation point pounds per square inch gage and 26.00 deactuation point pounds per square inch gage

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Pressure Connector Type:**

Plain, threaded external single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A048b0