

View Online at <https://aerobasegroup.com/nsn/5930-01-120-3591>

Hazardous Locations/environmental Protection:

Moisture resistant and vibration resistant

Overall Length:

4.220 inches

Outside Diameter:

0.250 inches single connection

Body Diameter:

1.560 inches

Overall Diameter:

1.870 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -45.6 degrees celsius and 71.0 degrees celsius

Mounting Method:

Inlet connection

Contact Action Stimulus:

Increase

Proof Pressure:

1000.00 pounds per square inch gage

Thread Size:

0.250 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 amperes resistive load single voltage and 3.0 amperes inductive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

29.50 actuation point pounds per square inch gage and 26.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A048b0