

View Online at <https://aerobasegroup.com/nsn/5930-01-120-5104>

Thread Class:

2a single threaded stud

Hazardous Locations/environmental Protection:

Explosion proof and moisture resistant and salt spray resistant

Overall Height:

0.839 inches

Body Height:

Between 0.399 inches and 0.437 inches

Overall Diameter:

Between 0.558 inches and 0.600 inches

Temperature Sensing Element Type:

Internal sensor

Mounting Method:

Threaded stud

Features Provided:

Hermetically sealed case

Thready Qty Per Inch (tpi):

32 single threaded stud

Contact Action Stimulus:

Increase

Thread Size:

0.138 inches single threaded stud

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

6.0 amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 1.0 amperes lamp load second voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

59.00 actuation point degrees fahrenheit and 105.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc

Thread Series Designator:

Unc single threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0