

View Online at <https://aerobasegroup.com/nsn/5930-01-120-5170>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

Between 2.270 inches and 2.330 inches

Overall Diameter:

1.500 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.250 inches single mounting facility

Operating Temperature Range:

-65.0/+125.0 degrees celsius

End Application:

Multi-hull bo 03950

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

2 single section front

Mounting Method:

Threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 ac at sea level

Rotor Through Connection Quantity:

1 single section

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

30.0 milliamperes resistive load ac at sea level

Special Features:

Replacement key 67-1918-20

Style Designator:

Miniature, pin mount

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0