

View Online at <https://aerobasegroup.com/nsn/5930-01-120-5172>

**Body Style:**

Bushing mount

**Overall Length:**

0.625 inches

**Overall Height:**

1.295 inches

**Overall Width:**

0.270 inches

**Bushing Length:**

0.280 inches

**Body Length:**

0.500 inches

**Body Width:**

0.270 inches

**Body Height:**

0.350 inches

**Case Material:**

Plastic

**Actuator Style:**

Round

**Actuator Diameter:**

0.105 inches

**Actuator Height:**

0.200 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

20.0 ac and 20.0 dc

**End Application:**

Rp-270/u

**Mounting Surface To Terminal End Distance:**

0.815 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded bushing

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

400.000 milliamperes resistive dc and 400.000 milliamperes resistive ac

**Special Features:**

Unthreaded bushing w/right angle printed circuit board mtd

**Precious Material And Location:**

Contacts and terminal surfaces gold

**Terminal Type And Quantity:**

3 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0