

View Online at <https://aerobasegroup.com/nsn/5930-01-120-5173>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

0.270 inches

Overall Height:

1.350 inches

Overall Width:

0.625 inches

Bushing Length:

0.280 inches

Body Length:

0.270 inches

Body Width:

0.500 inches

Body Height:

0.500 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.105 inches

Actuator Height:

0.270 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Actuator Color:

Natural single actuator

Maximum Voltage Rating In Volts:

20.0 ac and 20.0 dc

End Application:

Rp-270/u 11530

Mounting Surface To Terminal End Distance:

0.800 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded bushing

Nonpile-up Contact Arrangement:

1 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

400.000 milliamperes resistive dc and 400.000 milliamperes resistive ac

Special Features:

Non-thd bushing; epoxy sealed terminals; vertical mtg

Precious Material And Location:

Contacts and terminal surfaces gold

Terminal Type And Quantity:

3 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0