

View Online at <https://aerobasegroup.com/nsn/5930-01-120-8820>

Overall Height:

5.125 inches

Overall Width:

2.938 inches

Body Height:

5.125 inches

Unthreaded Mounting Hole Diameter:

0.266 inches

Distance Between Mounting Facility Centers:

5.750 inches

End Application:

Ticonderoga class cg (47), spruance class dd (963), kidd class ddg, yellowstone class ad-41, wasp class lhd

Tempurature Sensing Element Type:

Internal sensor

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port and manual reset button

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Criticality Code Justification:

Feat

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

-30.00/+1100.00 actuation point degrees fahrenheit and -30.00/+1100.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Voltage Rating In Volts:

250.0 ac at sea level single voltage

Special Features:

Weapon system essential

Media For Which Designed:

Gas or liquid

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0