

View Online at <https://aerobasegroup.com/nsn/5930-01-120-8820>

**Overall Height:**

5.125 inches

**Overall Width:**

2.938 inches

**Body Height:**

5.125 inches

**Unthreaded Mounting Hole Diameter:**

0.266 inches

**Distance Between Mounting Facility Centers:**

5.750 inches

**End Application:**

Ticonderoga class cg (47), spruance class dd (963), kidd class ddg, yellowstone class ad-41, wasp class lhd

**Temperature Sensing Element Type:**

Internal sensor

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port and manual reset button

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Criticality Code Justification:**

Feat

**Terminal Type:**

Screw

**Contact Load Current Rating:**

15.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

-30.00/+1100.00 actuation point degrees fahrenheit and -30.00/+1100.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

Internal deactuation point screw and internal actuation point screw

**Contact Voltage Rating In Volts:**

250.0 ac at sea level single voltage

**Special Features:**

Weapon system essential

**Media For Which Designed:**

Gas or liquid

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0