

View Online at <https://aerobasegroup.com/nsn/5930-01-120-9175>

**Thread Class:**

2b single mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

Between 2.270 inches and 2.330 inches

**Overall Diameter:**

1.500 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

1.250 inches single mounting facility

**Operating Temperature Range:**

-65.0/+125.0 degrees celsius

**End Application:**

Multi-hull bo 03950

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section front

**Throw Quantity:**

2 single section rear

**Mounting Method:**

Threaded hole single mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.138 inches single mounting facility

**Contact Voltage Rating In Volts:**

30.0 ac at sea level

**Rotor Through Connection Quantity:**

1 single section

**Mounting Facility Pattern:**

Two position in-line single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

30.0 milliamperes resistive load ac at sea level

**Special Features:**

Replacement key 11-1941-2

**Style Designator:**

Miniature, pin mount

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0