

View Online at <https://aerobasegroup.com/nsn/5930-01-120-9177>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.780 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.380 inches

Overall Height:

0.520 inches

Overall Width:

0.250 inches

Body Length:

0.780 inches

Body Width:

0.250 inches

Body Height:

0.390 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.087 inches

Actuator Style:

Round

Actuator Height:

0.060 inches

Actuator Free Position Height:

0.330 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Vehicle ecs

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

Between 3.0 ounces and 5.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.005 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0