NSN 5930-01-120-9178

Push Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-01-120-9178 | |
|---|--|
| Body Style: | |
| Panel mount | |
| Hazardous Locations/environmental Protection: | |
| Weatherproof | |
| Overall Length: | |
| 0.740 inches | |
| Overall Height: | |
| 3.060 inches | |
| Overall Width: | |
| 0.740 inches | |
| Body Diameter: | |
| 0.740 inches | |
| Body Height: | |
| 2.760 inches | |
| Case Material: | |
| Metal | |
| Actuator Length: | |
| 0.740 inches | |
| Actuator Style: | |
| Rectangular | |
| Actuator Width: | |
| 0.740 inches | |
| Actuator Color: | |
| White single actuator | |
| Illuminated Actuator Color: | |
| Red single actuator | |
| Maximum Voltage Rating In Volts: | |
| 200.0 ac and 28.0 dc | |
| End Application: | |
| Multi-hull bo 03950 | |
| Inclosure Type: | |
| Fully enclosed | |
| Mounting Method: | |
| Panel | |
| Features Provided: | |
| Actuator seal and rfi shielding | |
| Nonpile-up Contact Arrangement: | |
| 2 pole, double throw, one position momentary single switch unit | |
| Contact Load Current Rating At Maximum Rated Voltage: | |

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac

Special Features:

Case internally grounded

NSN 5930-01-120-9178

Push Switch - Page 2 of 2



| Terminal Ty | pe And | Quantity: |
|-------------|--------|-----------|
| | | |

12 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0