

View Online at <https://aerobasegroup.com/nsn/5930-01-121-7066>

Overall Length:

3.250 inches

Overall Width:

3.680 inches

Dc Voltage Rating:

Between 18.0 volts and 30.0 volts

Connector Manufacturer Code:

81349

Specific Equipment Accommodated:

Ch53e helicopter

Actuation Method:

Buoyancy

End Application:

Helicopter, ch-53a/d/e; helicopter, mh-53e; helicopter, ch-53a/d/e

Electrical Connection Type:

Connector receptacle

Connector Identification:

Mil-c-5015

Internal Battery Accommodation:

Not included

Current Rating At Maximum Rated Voltage:

0.5 amperes resistive load

Voltage Rating At Maximum Rated Current:

28.0 volts

Float Quantity:

1

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit

Mounting Method:

Flange

Mounting Position:

Horizontal

Maximum Current Rating:

0.5 amperes resistive load

Contact Arrangement:

Single throw, normally open, normally closed

Relay:

Not included

Liquid Type For Which Designed:

Lubricating oil

Float Effective Travel:

Any acceptable

Mounting Dimensions:

Mtd by four no. 10-32 nf-2b self-locking inserts, three of which are equally spaced 1.312 in. C to c and one 1.187 in. C to c with first insert

Tank Insertion Length:

2.500 inches

Criticality Code Justification:

Feat

Special Features:

Weapon system essential

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T109-d

Mil-std (military Standard):

Mil-c-5015 spec.