

View Online at <https://aerobasegroup.com/nsn/5930-01-121-7655>

Thread Class:

2b single pressure connection

Inside Diameter:

0.438 inches single connection

Overall Length:

2.250 inches

Overall Height:

4.875 inches

Overall Width:

2.250 inches

Body Diameter:

2.000 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Longest Horizontal Distance Between Mounting Centers:

1.812 inches

Longest Vertical Distance Between Mounting Centers:

1.812 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -40.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Flange and unthreaded hole

Features Provided:

Electrical box connector

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Decrease

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

3.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+1500.00/+3500.00 actuation point pounds per square inch gage and +1500.00/+3500.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Stimulus Rating:

2000.00 actuation point pounds per square inch and 2200.00 deactuation point pounds per square inch and 200.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0