NSN 5930-01-121-7662

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-121-7662
Overall Height:
0.669 inches
Body Diameter:
0.640 inches
Mounting Slot Width:
Between 0.143 inches and 0.147 inches
Body Height:
0.358 inches
Unthreaded Mounting Hole Diameter:
Between 0.137 inches and 0.147 inches
Distance Between Mounting Facility Centers:
Between 0.930 inches and 0.944 inches
End Application:
Oe236delta81
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating:
71.0 degrees celsius and -54.0 degrees celsius
Mounting Method:
Bracket and unthreaded hole and slot
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
2.0 amperes resistive load second voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
170.00 actuation point degrees fahrenheit and 155.00 deactuation point degrees fahrenheit and 156.00 deactuation point degrees
fahrenheit and 14.00 differential point degrees fahrenheit and 15.00 differential point degrees fahrenheit
Contact Voltage Rating In Volts:
28.0 dc at sea level second voltage
Media For Which Designed:
Gas or liquid
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5930-01-121-7662

Thermostatic Switch - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A048b0