NSN 5930-01-121-7870

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-121-7870 **Thread Class:** 2b **Body Style:** Rh access cover **Hazardous Locations/environmental Protection:** Watertight **Overall Width:** 2.312 inches **Actuator Style:** Roller arm **Housing Height:** 2.000 inches **Housing Length:** 5.000 inches **Housing Width:** 2.312 inches **Center To Center Distance Between Housing Mounting Facilities Parallel To Length:** 2.625 inches **Maximum Voltage Rating In Volts:** 240.0 ac and 240.0 dc **End Application:** Mk5mod5 **Inclosure Type:** Hermetically sealed **Mounting Method:** Threaded hole **Features Provided:** Actuator seal Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.250 inches **Nonpile-up Contact Arrangement:** 2 pole, double throw, one position momentary single switch unit **Switch Release Force:** 16.0 inch-ounces **Switch Actuating Force:** 192.0 inch-ounces **Actuator Movement:**

Contact Load Current Rating At Maximum Rated Voltage:

10.0 pretravel degrees and 70.0 overtravel degrees

500.000 milliamperes resistive dc and 3.000 amperes resistive ac

NSN 5930-01-121-7870 Sensitive Switch - Page 2 of 2



Thread Series Designator:
Unc
Terminal Type And Quantity:
6 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0