NSN 5930-01-121-9451

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-121-9451
Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Watertight
Overall Width:
2.312 inches
Actuator Style:
Roller arm
Housing Height:
2.000 inches
Housing Length:
5.000 inches
Housing Width:
2.312 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
4.220 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.810 inches
Maximum Voltage Rating In Volts:
240.0 ac and 240.0 dc
End Application:
Mk5mod5
Inclosure Type:
Hermetically sealed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:

16.0 inch-ounces

Switch Actuating Force:

192.0 inch-ounces

Actuator Movement:

10.0 pretravel degrees and 70.0 overtravel degrees

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 3.000 amperes resistive ac

Special Features:

Left hand switching action

Terminal Type And Quantity:

6 screw

NSN 5930-01-121-9451

Sensitive Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0