## NSN 5930-01-122-0298

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-122-0298

#### **Body Style:**

Panel mount

#### Hazardous Locations/environmental Protection:

Moisture proof and shock proof

#### **Overall Length:**

0.755 inches

#### **Overall Height:**

3.060 inches

#### **Overall Width:**

0.755 inches

#### **Body Length:**

0.755 inches

#### **Body Width:**

0.755 inches

## Body Height:

Body Holght.

### 2.250 inches

Case Material:

Metal

#### Actuator Length:

0.755 inches

#### Actuator Style:

Rectangular

#### Actuator Width:

0.755 inches

#### Actuator Color:

Green single actuator

#### **Illuminated Actuator Color:**

Green single actuator

#### **Actuator Inscription:**

Open hull ovbd equalizing valve single actuator

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

#### **Features Provided:**

Actuator seal

#### Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

#### Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes

inductive ac and 1.500 amperes lamp ac



# NSN 5930-01-122-0298

Push Switch - Page 2 of 2



Special Features:

Full display lens

**Precious Material And Location:** 

Contact surfaces gold and contacts silver

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

19 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0