

View Online at <https://aerobasegroup.com/nsn/5930-01-122-0319>

Thread Class:

2a 1st mounting facility

Thread Length:

0.188 inches 1st mounting facility

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

6.375 inches

Overall Height:

4.750 inches

Overall Width:

4.750 inches

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

1.625 inches single actuator

Unthreaded Mounting Hole Diameter:

0.406 inches 2nd mounting facility and 0.410 inches 2nd mounting facility

Individual Section Quantity:

3

Knob Manufacturer Code:

82121

Longest Horizontal Distance Between Mounting Centers:

3.781 inches 2nd mounting facility

Longest Vertical Distance Between Mounting Centers:

3.781 inches 2nd mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

3 each section rear

Mounting Method:

Threaded bushing 1st mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

32 1st mounting facility

Thread Size:

0.469 inches 1st mounting facility

Contact Voltage Rating In Volts:

450.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular 2nd mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

60.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Uns 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0