

View Online at <https://aerobasegroup.com/nsn/5930-01-122-1567>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

4.200 inches

Overall Height:

2.440 inches

Overall Width:

1.880 inches

Actuator Style:

Flexible

Actuator Diameter:

7.3 millimeters

Actuator Height:

0.690 inches

Housing Height:

1.700 inches

Housing Length:

4.200 inches

Housing Width:

1.880 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.340 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.160 inches

Maximum Voltage Rating In Volts:

600.0 ac and 240.0 dc

End Application:

Compressor ai 93236

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, both positions maintained single switch unit

Switch Actuating Force:

64.0 ounces

Actuator Movement:

Between 65.0 pretravel degrees and 20.0 overtravel degrees and 30.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

400.000 milliamperes resistive dc and 150.000 milliamperes inductive dc and 6.000 amperes resistive ac

Special Features:

Non-plug-in 0.750 in. Conduit

Terminal Type And Quantity:

8 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0