NSN 5930-01-122-1567

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-122-1567

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
4.200 inches
Overall Height:
2.440 inches
Overall Width:
1.880 inches
Actuator Style:
Flexible
Actuator Diameter:
7.3 millimeters
Actuator Height:
0.690 inches
Housing Height:
1.700 inches
Housing Length:
4.200 inches
Housing Width:
1.880 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.340 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.160 inches
Maximum Voltage Rating In Volts:
600.0 ac and 240.0 dc
End Application:
Compressor ai 93236
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
2 two circuit, double break/double make, both positions maintained single switch unit
Switch Actuating Force:
64.0 ounces
Actuator Movement:
Between 65.0 pretravel degrees and 20.0 overtravel degrees and 30.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

 $400.000 \ \text{milliamperes resistive dc and } 150.000 \ \text{milliamperes inductive dc and } 6.000 \ \text{amperes resistive ac}$

NSN 5930-01-122-1567

Sensitive Switch - Page 2 of 2



Non-plug-in 0.750 in. Conduit

Terminal Type And Quantity:

8 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0