

View Online at <https://aerobasegroup.com/nsn/5930-01-122-1568>

Body Style:

Bushing/hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

1.940 inches

Body Width:

0.687 inches

Body Height:

0.990 inches

Unthreaded Mounting Hole Diameter:

0.139 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

1.312 inches

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

0.190 inches

Maximum Voltage Rating In Volts:

480.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing and unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 7.0 ounces and 10.0 ounces

Actuator Movement:

0.015 pretravel inches and 0.140 overtravel inches and 0.001 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

22.000 amperes resistive ac

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0