

View Online at <https://aerobasegroup.com/nsn/5930-01-122-2288>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Shock proof

Overall Length:

4.062 inches

Overall Height:

2.875 inches

Overall Width:

2.500 inches

First Flat Length:

0.750 inches single actuator

Flat Height:

0.250 inches single actuator

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

1.187 inches single actuator

Individual Section Quantity:

2

Knob Manufacturer Code:

27192

Knob Manufacturer Part Number:

A53-527-3

Longest Horizontal Distance Between Mounting Centers:

1.062 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.062 inches single mounting facility

End Application:

Multi-hull

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded hole single mounting facility

Features Provided:

Actuator knob and metallic inclosure

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

440.0 highest ac voltage rating at sea level

Switch Actuator Momentary Position:

Clockwise single actuator and counterclockwise single actuator

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Screw

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Contact Load Current Rating:

4.0 amperes inductive load lowest ac voltage rating at sea level

Style Designator:

In-line, cam actuated

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A052b0