NSN 5930-01-122-4029

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Shock resistant and vibration resistant

Body Style:Panel mounted

Overall Length: 3.047 inches Overall Height:



View Online at https://aerobasegroup.com/nsn/5930-01-122-4029

0.870 inches
Overall Width:
0.870 inches
Body Length:
2.750 inches
Body Width:
0.870 inches
Body Height:
0.870 inches
Case Material:
Metal
Actuator Length:
0.730 inches
Actuator Style:
Rectangular
Actuator Height:
0.296 inches
Actuator Width:
0.730 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Green single actuator
Actuator Inscription:
Measure monitor single actuator
Maximum Voltage Rating In Volts:
230.0 ac and 28.0 dc
End Application:
4920-01-054-8585 test adapter, interface
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Full display lens

NSN 5930-01-122-4029

Push Switch - Page 2 of 2



Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

3 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0