# NSN 5930-01-122-4030

Push Switch - Page 1 of 2

**Body Style:**Panel mounted



View Online at https://aerobasegroup.com/nsn/5930-01-122-4030

Hazardous Locations/environmental Protection:
Shock resistant and vibration resistant
Overall Length:
3.047 inches
Overall Height:
0.870 inches
Overall Width:
0.870 inches
Body Length:
2.750 inches
Body Width:
0.870 inches
Body Height:
0.870 inches
Case Material:
Metal
Actuator Length:
0.730 inches
Actuator Style:
Rectangular
Actuator Height:
0.296 inches
Actuator Width:
0.730 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Green single actuator
Actuator Inscription:
Station resource monitor single actuator
Maximum Voltage Rating In Volts:
230.0 ac and 28.0 dc
End Application:
4920-01-054-8585 test adapter, interface
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Full display lens

## NSN 5930-01-122-4030

Push Switch - Page 2 of 2



## Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

### **Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac

**Precious Material And Location:** 

Contacts gold

### **Terminal Type And Quantity:**

3 turret and 5 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0