

View Online at <https://aerobasegroup.com/nsn/5930-01-122-4032>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

3.047 inches

Overall Height:

0.870 inches

Overall Width:

0.870 inches

Body Length:

2.750 inches

Body Width:

0.870 inches

Body Height:

0.870 inches

Case Material:

Metal

Actuator Length:

0.730 inches

Actuator Style:

Rectangular

Actuator Height:

0.296 inches

Actuator Width:

0.730 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

Green single actuator

Actuator Inscription:

No go single actuator

Maximum Voltage Rating In Volts:

230.0 ac and 28.0 dc

End Application:

4920-01-054-8585 test adapter, interface

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Full display lens

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

3 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0