NSN 5930-01-122-4034

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Shock resistant and vibration resistant

Body Style: Panel mount

Overall Length: 0.870 inches Overall Height: 3.046 inches Overall Width:



View Online at https://aerobasegroup.com/nsn/5930-01-122-4034

0.870 inches				
Body Length:				
0.870 inches				
Body Width:				
0.870 inches				
Body Height:				
2.160 inches				
Case Material:				
Metal				
Actuator Length:				
0.730 inches				
Actuator Style:				
Rectangular				
Actuator Height:				
0.296 inches				
Actuator Width:				
0.730 inches				
Actuator Color:				
Green single actuator				
Illuminated Actuator Color:				
Green single actuator				
Actuator Inscription:				
Stop single actuator				
Maximum Voltage Rating In Volts:				
230.0 ac and 28.0 dc				
End Application:				
4920-01-054-8585				
Inclosure Type:				
Fully enclosed				
Nonpile-up Contact Arrangement:				
1 pole, double throw, one position momentary single switch unit				
Contact Load Current Rating At Maximum Rated Voltage:				
7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac				

NSN 5930-01-122-4034

Push Switch - Page 2 of 2



Preci	ious	Material	And	Location:
-------	------	----------	-----	-----------

Contacts gold

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0