

View Online at <https://aerobasegroup.com/nsn/5930-01-122-4036>

**Body Style:**

Panel mounted

**Hazardous Locations/environmental Protection:**

Shock resistant and vibration resistant

**Overall Length:**

3.047 inches

**Overall Height:**

0.870 inches

**Overall Width:**

0.870 inches

**Body Length:**

2.750 inches

**Body Width:**

0.870 inches

**Body Height:**

0.870 inches

**Case Material:**

Metal

**Actuator Length:**

0.730 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.296 inches

**Actuator Width:**

0.730 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

Green single actuator

**Actuator Inscription:**

Indicate measured value single actuator

**Maximum Voltage Rating In Volts:**

230.0 ac and 28.0 dc

**End Application:**

4920-01-054-8585 test adapter, interface

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Full display lens

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac

**Precious Material And Location:**

Contacts gold

**Terminal Type And Quantity:**

3 turret and 5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0