

View Online at <https://aerobasegroup.com/nsn/5930-01-122-4235>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.312 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

4.412 inches

**First Flat Length:**

0.467 inches single actuator

**Flat Height:**

0.219 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.812 inches single actuator

**Overall Diameter:**

1.400 inches

**Individual Section Quantity:**

5

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

4 each section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

0.5 amperes resistive load dc at sea level and 250.0 milliamperes inductive load dc at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0