

View Online at <https://aerobasegroup.com/nsn/5930-01-122-4239>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Oiltight

Overall Height:

3.250 inches

Overall Width:

2.120 inches

Actuator Style:

Roller arm

Actuator Roller Diameter:

0.880 inches

Actuator Roller Width:

0.300 inches

Housing Height:

1.760 inches

Housing Length:

6.000 inches

Housing Width:

2.120 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

3.380 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.500 inches

Maximum Voltage Rating In Volts:

600.0 ac and 230.0 dc

End Application:

3930-01-069-1026

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Actuating Force:

48.0 ounces

Actuator Movement:

Between 12.0 pretravel degrees and 60.0 overtravel degrees and 4.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 20.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0