## NSN 5930-01-122-4239

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-122-4239

Body Style:				
Hole mounted				
Hazardous Locations/environmental Protection:				
Oiltight				
Overall Height:				
3.250 inches				
Overall Width:				
2.120 inches				
Actuator Style:				
Roller arm				
Actuator Roller Diameter:				
0.880 inches				
Actuator Roller Width:				
0.300 inches				
Housing Height:				
1.760 inches				
Housing Length:				
6.000 inches				
Housing Width:				
2.120 inches				
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:				
3.380 inches				
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:				
1.500 inches				
Maximum Voltage Rating In Volts:				
600.0 ac and 230.0 dc				
End Application:				
3930-01-069-1026				
Inclosure Type:				
Fully enclosed				
Mounting Method:				
Unthreaded hole				
Features Provided:				
Actuator seal				
Nonpile-up Contact Arrangement:				
1 pole, double throw, one position momentary single switch unit				
Switch Actuating Force:				
48.0 ounces				
Actuator Movement:				
Between 12.0 pretravel degrees and 60.0 overtravel degrees and 4.0 differential degrees				

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 20.000 amperes resistive ac

## NSN 5930-01-122-4239

Sensitive Switch - Page 2 of 2



Termina	I Type	And	Quantity:

3 screw

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0