NSN 5930-01-122-4243

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-122-4243

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
0.750 inches
Overall Height:
3.096 inches
Overall Width:
0.750 inches
Body Length:
0.679 inches
Body Width:
0.750 inches
Body Height:
2.950 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.100 inches
Actuator Width:
0.620 inches
Actuator Color:
Natural single actuator
Illuminated Actuator Color:
Natural single actuator
Actuator Inscription:
Unload single actuator
Maximum Voltage Rating In Volts:
28.0 dc
End Application:
Hull obrp
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Namela un Cantact Arrangement

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

NSN 5930-01-122-4243

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

8 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0