## NSN 5930-01-122-4580

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-122-4580

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Shock resistant and vibration resistant
Overall Length:
3.047 inches
Overall Height:
0.870 inches
Overall Width:
0.870 inches
Body Length:
2.750 inches
Body Width:
0.870 inches
Body Height:
0.870 inches
Case Material:
Metal
Actuator Length:
0.730 inches
Actuator Style:
Rectangular
Actuator Height:
0.296 inches
Actuator Width:
0.730 inches
Actuator Color:
Green single actuator
Illuminated Actuator Color:
Green single actuator
Actuator Inscription:
Repeat test single actuator
Maximum Voltage Rating In Volts:
230.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Full display lens
Nonpile-up Contact Arrangement:
1 note double throw one position momentary single switch unit

1 pole, double throw, one position momentary single switch unit

## NSN 5930-01-122-4580

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac

**Precious Material And Location:** 

Contacts gold

**Terminal Type And Quantity:** 

3 turret and 5 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0