NSN 5930-01-122-4581

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-122-4581

| Body Style: |
|---|
| Panel mount |
| Hazardous Locations/environmental Protection: |
| Shock resistant and vibration resistant |
| Overall Length: |
| 0.870 inches |
| Overall Height: |
| 3.046 inches |
| Overall Width: |
| 0.870 inches |
| Body Length: |
| 0.870 inches |
| Body Width: |
| 0.870 inches |
| Body Height: |
| 2.160 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| 0.730 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.296 inches |
| Actuator Width: |
| 0.730 inches |
| Actuator Color: |
| Green single actuator |
| Illuminated Actuator Color: |
| Green single actuator |
| Actuator Inscription: |
| Single test single actuator |
| Maximum Voltage Rating In Volts: |
| 230.0 ac and 28.0 dc |
| End Application: |
| F16aircombfit |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |

NSN 5930-01-122-4581

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0