

View Online at <https://aerobasegroup.com/nsn/5930-01-123-0779>

Overall Length:

5.750 inches

Overall Height:

10.938 inches

Overall Width:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

3.000 inches

Shortest Horizontal Distance Between Mounting Centers:

1.062 inches

Longest Vertical Distance Between Mounting Centers:

4.250 inches

End Application:

Hull obrp

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes inductive load fourth voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+500.00/+5000.00 actuation point pounds per square inch gage and +500.00/+5000.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

550.0 dc at sea level third voltage

Pressure Connector Type:

Plain, threaded external single connection

Media For Which Designed:

Gas or liquid

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0