

View Online at <https://aerobasegroup.com/nsn/5930-01-123-1471>

Thread Class:

2a

Hazardous Locations/environmental Protection:

Watertight

Bushing Length:

0.562 inches

Body Length:

0.690 inches

Body Width:

0.850 inches

Body Height:

0.380 inches

Actuator Style:

Round

Actuator Diameter:

0.125 inches

Actuator Height:

0.320 inches

Actuator Free Position Height:

0.882 inches

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

6625-01-034-0942

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.375 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

8.0 ounces

Switch Actuating Force:

40.0 ounces

Actuator Movement:

Between 0.070 pretravel inches and 0.187 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 7.500 amperes inductive dc and 4.000 amperes motor dc

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

4 tab, solder lug

Specification Data:

81349-mil-s-8805/84 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0